

HARDWIRED SMOKE DETECTOR**VS-YY500 Hardwired Smoke Detector (4 wires)****KEY FEATURES**

- MCU processing adopted
- Auto-reset or reset by power off
- Strong adaptability for circumstance
- SMT Design, High Stability
- 9-35V DC wide voltage operating range
- Low standby current
- Stainless steel shield, anti-RFI(20V/m-1GHz)
- Dustproof, mothproof, anti-white light

PARAMETERS

Operating voltage: DC 9V-35V

Standby current: 55uA

Alarm current: 35mA@ DC12V

Alarm indication: red LED on

Operating temperature: -10 +50

Operating humidity: 95% RH

Alarm output: relay output (NC, NO)

Sensitivity: class I

Dimension size: 104 mm* 47mm deep

**HARDWIRED SMOKE DETECTOR****VS-YY700 Hardwired Smoke Detector (4 wires)****KEY FEATURES**

- ASIC control, Special chamber design has greatly decreased dust levels.
- Manual test, auto-reset
- Infrared photoelectric sensor and improved detection accuracy
- Network output (NC,NO) / LED indicator
- Dustproof, mothproof, anti-light interference
- Strong adaptability to circumstance
- Dustproof, mothproof and anti-white light
- Low power indication

PARAMETERS

Operating voltage: DC 9-16V

Standby current: less than 200uA

Alarm current: less than 20mA

Operating temp.: -10 to +50

Working humidity: less than 95% RH

Detecting area: 20 square meter

orking environment: -10 - +50 ;95%RH

Dimension: 100mm .*55mm deep

